

D-SUB I.D.C. TYPE

Position	A	B	C	D	E
9	17.78	24.99	30.82	11.86	16.33
15	26.15	33.32	39.24	19.50	24.66
25	39.94	47.04	53.04	32.15	38.38
37	56.56	63.50	69.62	48.76	54.84

XX: Nr.PIN Y: M-Male / F-Female


PART NO: SM C05 0580 XX YCB-Low

TITLE: D-SUB FEMALE DUAL ROW IDC TYPE CONNECTOR

NOTES:
 Current Rating: 3.0AMP
 Withstand Voltage: 500V AC/DC
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Operation Temperature: -55°C to +105°C

Insulator Material: PBT+30%GF(UL94V-0)
 Contact Material: Brass
 Contact Plating: AU Over Ni
 Shell: Cold Roller Steel, Ni Plated

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN METRIC TOLERANCES ARE:
 DECIMALS Angle
 X.X: ±0.40 ± 3°
 X.XX: ±0.25
 X.XXX: ±0.15

SCALE 1:1
 UNIT MM
 PROJ. 
 SHEET

A0	2015/06/25	NEW	Hua.ZT		Hua.ZT
REV	DATE	MODIFICATION DESCRIPTION	DRAW	CHANGE	APPROVE