



Electrical

Voltage: 50 V AC(rms) /DC
 Current: 0.5 A AC(rms) /DC
 Contact Resistance: 20 mΩ max (Initial)
 Dielectric Withstanding Voltage: 250 V AC/rms
 Insulation Resistance: 50 MΩ min
 Operating Temp: -20° C ~ +85° C

P	A	B	C	P	A	B	C
4	1,500	2,600	8,400	35	17,000	18,100	23,900
5	2,000	3,100	8,900	36	17,500	18,600	24,400
6	2,500	3,600	9,400	37	18,000	19,100	24,900
7	3,000	4,100	9,900	38	18,500	19,600	25,400
8	3,500	4,600	10,400	39	19,000	20,100	25,900
9	4,000	5,100	10,900	40	19,500	20,600	26,400
10	4,500	5,600	11,400	41	20,000	21,100	26,900
11	5,000	6,100	11,900	42	20,500	21,600	27,400
12	5,500	6,600	12,400	43	21,000	22,100	27,900
13	6,000	7,100	12,900	44	21,500	22,600	28,400
14	6,500	7,600	13,400	45	22,000	23,100	28,900
15	7,000	8,100	13,900	46	22,500	23,600	29,400
16	7,500	8,600	14,400	47	23,000	24,100	29,900
17	8,000	9,100	14,900	48	23,500	24,600	30,400
18	8,500	9,600	15,400	49	24,000	25,100	30,900
19	9,000	10,100	15,900	50	24,500	25,600	31,400
20	9,500	10,600	16,400	51	25,000	26,100	31,900
21	10,000	11,100	16,900	52	25,500	26,600	32,400
22	10,500	11,600	17,400	53	26,000	27,100	32,900
23	11,000	12,100	17,900	54	26,500	27,600	33,400
24	11,500	12,600	18,400	55	27,000	28,100	33,900
25	12,000	13,100	18,900	56	27,500	28,600	34,400
26	12,500	13,600	19,400	57	28,000	29,100	34,900
27	13,000	14,100	19,900	58	28,500	29,600	35,400
28	13,500	14,600	20,400	59	29,000	30,100	35,900
29	14,000	15,100	20,900	60	29,500	30,600	36,400
30	14,500	15,600	21,400	61	30,000	31,100	36,900
31	15,000	16,100	21,900	62	30,500	31,600	37,400
32	15,500	16,600	22,400	63	31,000	32,100	37,900
33	16,000	17,100	22,900	64	31,500	32,600	38,400
34	16,500	17,600	23,400				



TOLERANCES
 X ±0.15 XX ±0.08
 ANNOTES
 1st

PC05H-2.0		09/09/05	
(DRAWING NO)		(CHKD)	
SM C06 88001-XX-V		(APPD)	
(THRU)	(SCALE)	(DUNNG)	(SIZE)
---	1:1	MM	1 OF 1
REV	REVISION DESCRIPTION	DATE	SIGNATURE
---	---	---	---