



|                      |                                       |                        |
|----------------------|---------------------------------------|------------------------|
| Standard             | UL                                    | CE                     |
| Rated voltage        | 300V                                  | 750V                   |
| Rated current        | 20A                                   | 41A                    |
| Wire range           | 20-10AWG                              | 0.5-6.0mm <sup>2</sup> |
| Withstanding voltage | AC3000V/1Min                          |                        |
| Torque               | 1.2Nm(10.6Lb-In.)                     |                        |
| Ambient temperature  | -40°C~+105°C                          |                        |
| Pitch                | 7.50mm (.295")                        |                        |
| Poles                | 1P ,2P                                |                        |
| Housing              | PA66,UL94V-0                          |                        |
| Screws               | M4.0,steel,Cr <sup>3+</sup> Zn plated |                        |
| Terminals            | Brass, Ni-Plated                      |                        |

**RoHS  
Compliant**

**SCHMID-M**

|       |        |           |
|-------|--------|-----------|
| APPD. |        | TOLERANCE |
| DWG.  |        | SCALE     |
| DATE  | UNIT   | SIZE.     |
|       | PAGE   | REV.      |
|       | M M    | A 4       |
|       | 1 OF 1 | A         |

Part Name:  
Transformer Terminal Block Pitch:7,5mm 750V/41A  
Wire: 0,5-6,0mm<sup>2</sup>

Part Nr: SM C09 77510 XX