



|                      |                                       |                    |
|----------------------|---------------------------------------|--------------------|
| Standard             | UL                                    | VDE                |
| Rated voltage        | 350V                                  | 250V               |
| Rated current        | 15A                                   | 18A                |
| Wire range           | 24-12AWG                              | 2.5mm <sup>2</sup> |
| Withstanding voltage | AC2000V/1Min                          |                    |
| Ambient temperature  | -40°C~+105°C                          |                    |
| Strip length         | 7mm                                   |                    |
| Torque               | 0.4Nm(3.5Lb-In.)                      |                    |
| Pitch                | 5.00 / 5.08 / 7.50 / 10.00 mm(.197")  |                    |
| Poles                | 2P , 3P ---Any poles                  |                    |
| Housing              | PA66,UL94V-0                          |                    |
| Screws               | M2.5,steel,Cr <sup>3+</sup> Zn plated |                    |
| Solder Pins          | Brass, Tin plated                     |                    |
| Contact Cage         | Brass, Ni plated                      |                    |

|                 |             |                         |   |
|-----------------|-------------|-------------------------|---|
| RoHS Compliant  |             | <b>SCHMID-M</b>         |   |
| APPD.           |             | TOLERANCE               | PART NAME   |
| DWG. GRAY       | SCALE       | .0 ±<br>.00 ±<br>ANG. ± | Terminal Block, Screw Clamp Style, Hor. Cond.,<br>Pitch 7,50mm, PCB Straight,<br>XX..... Nr. Pins |
| DATE 2014/01/30 | UNIT M M    | SIZE A 4                | PART NO.  |
|                 | PAGE 1 OF 1 | REV. A                  | SM C09 1757 XX SS4  |