



|                      |                                       |                    |
|----------------------|---------------------------------------|--------------------|
| Standard             | UL                                    | VDE                |
| Rated voltage        | 300V                                  | 250V               |
| Rated current        | 12A                                   | 15A                |
| Wire range           | 26-14AWG                              | 1.5mm <sup>2</sup> |
| Withstanding voltage | AC2000V/1Min                          |                    |
| Ambient temperature  | -40°C~+105°C                          |                    |
| Strip length         | 5-6mm                                 |                    |
| Torque               | 0.4Nm(4.4Lb-In.)                      |                    |
| Pitch                | 5.00 / 5.08 mm(.197")                 |                    |
| Poles                | 2P , 3P ---Any poles                  |                    |
| Housing              | PA66,UL94V-0                          |                    |
| Screws               | M2.5,steel,Cr <sup>3+</sup> Zn plated |                    |
| Solder Pins          | Brass, Tin plated                     |                    |
| Contact Cage         | Brass, Ni plated                      |                    |



|                 |             |                 |  |
|-----------------|-------------|-----------------|--|
| RoHS Compliant  |             | <b>SCHMID-M</b> |  |
| APPD.           |             | TOLERANCE       | PART NAME                                      |
| DWG. GRAY       | SCALE       | .0 ±            | Terminal Block, Screw Clamp Style, Hor. Cond., |
| DATE 2014/01/30 | UNIT M M    | .00 ±           | Pitch 5,00mm, PCB Straight,                    |
|                 | PAGE 1 OF 1 | ANG. ±          | XX..... Nr. Pins                               |
|                 |             | SIZE. A 4       | PART NO.                                       |
|                 |             | REV. A          | SM C09 15009 XX SS4-A                          |