



|                      |   |                    |
|----------------------|---|--------------------|
| Standard             | UL                                      | VDE                |
| Rated voltage        | 300V                                    | 320V               |
| Rated current        | 15A                                     | 20A                |
| Wire range           | 28-12AWG                                | 2.5mm <sup>2</sup> |
| Withstanding voltage | AC2500V/1Min                            |                    |
| Ambient temperature  | (-)40°C to +105°C                       |                    |
| Strip length         | 7mm                                     |                    |
| Torque               | 0.4Nm(3.5Lb-In.)                        |                    |
| Pitch                | 5.00/5.08/7.50/7.62mm(.197")            |                    |
| Poles                | 2P, 3P --- Any poles                    |                    |
| Housing              | PA66, UL94V-0                           |                    |
| Screws               | M2.5, steel, Cr <sup>3+</sup> Zn plated |                    |
| Wire Cage            | Brass, Ni plated                        |                    |
| Contact Cage         | Brass, Ni plated                        |                    |

|                |             |                                  |  |
|----------------|-------------|----------------------------------|--|
| RoHS Compliant |             | <b>SCHMID-M</b>                  |  |
| APPD.          |             | TOLERANCE                        | PART NAME  |
| DWG. HELGA     | SCALE       | XX ± 0.25<br>XX ± 0.35<br>ANG. ± | Pluggable Terminal Block Wire Cage Terminal 5,00mm<br>Green With fix screw XX: No. Poles |
| DATE 2013/10   | UNIT M M    | SIZE. A 4                        | PART NO.   |
|                | PAGE 1 OF 1 | REV. C                           | SM C09 0504 XX YSC   |