

1

2

3

4

5

6

7

8

A

SM C09 UK-2.5-TW-PE



B

C

D

E

F

G


H

Part Number		SM C09 UK-2.5-TW-PE	SM C09 UK-4-TW-PE
Width/Thickness/Height (mm)		50.1/5.2/47	50.5/6.2/47
Screw (mm)		M3	M3
Torque (Nm)		0.6-0.8	0.6-0.8
Strip Length (mm)		7	8
Wire Size (mm ²)		0.2 - 2.5	0.2 - 4.0
Voltage (V)		300V	300V
Current (A)		20A	30A
Insulating Materials		PA, UL94V-0	PA, UL94V-0
Insertion Bridge	2P	EB 2-5N	EB 2-6
	3P	EB 3-5N	EB 3-6
	10P	EB 10-5N	EB 10-6
Zack Strip		ZB5	ZB6

SM C09 UK-4-TW-PE

RoHS
Compliant

APPD.



SCALE

TOLERANCE

X.XX± 0.25

X.X±0.35

ANG. ±

PART NAME

SM C09 UK-TW-PE Series

DWG.

UNIT

MM

SIZE

A4

DATE

2013/10

PAGE

1 OF 1

REV

C

PART NO.

1

2

3

4

5

6

7

8