


1 2 3 4 5 6 7 8

A

A

SM C09 UDK-2.5

End Cover



B

B

C

C

D

D

E

E


Part Number		SM C09 UDK-2.5	SM C09 UDK-4
Width/Thickness/Height (mm)		63.5/5.2/47	63.5/6.2/47
Screw (mm)		M3	M3
Torque (Nm)		0.6 - 0.8	0.6 - 0.8
Strip Length (mm)		8	8
Wire Size (mm <sup>2</sup> )		0.2 - 2.5	0.2 - 4.0
Voltage (V)		300V	300V
Current (A)		20A	30A
Insulating Materials		PA, UL94V-0	PA, UL94V-0
Fixed Bridge	2P	FBRI 2-5N	FBRI 2-6
	3P	FBRI 3-5N	FBRI 3-6
	4P	FBRI 4-5N	BRI 4-6
	10P	FBRI 10-5N	FBRI 10-6
Zack Strip		ZB5	ZB6

F

F

SM C09 UDK-4

End Cover



G

G

H

H

APPD. DWG. DATE 2013/10		RoHS Compliant		TOLERANCE X.XX± 0.25 X.X±0.35 ANG. ±	PART NAME SM C09 UDK Series
SCALE UNIT MM		TOLERANCE X.XX± 0.25 X.X±0.35 ANG. ±	PART NAME SM C09 UDK Series	PART NO.	PART NO.
PAGE 1 OF 1		UNIT MM	SIZE A4	REV C	PART NO.

1 2 3 4 5 6 7 8