

## 2M Cable assembly with a 3 Pole M12 Straight & 3 Pole M12, 4 A, 250 V, IP67



### Specifications:




Cable Shape	Multicore
Connector A Gender	Female
Connector A Number of Contacts	3
Connector A	M12 Straight
Connector B Gender	Male
Connector B Number of Contacts	3
Connector B	M12 Straight
Cross Sectional Area	0.34 mm <sup>2</sup>
Current Rating	4 A
IP Rating	IP67
Length	2 m
Maximum Operating Temperature	+75°C
Minimum Operating Temperature	-25°C
Number of Cores	3
Operating Temperature Range	-25 to +75°C
Outer Diameter	4.5 mm
Outer Sheath Material	PVC
Sheath Colour	Black
Sheath Material	PVC
Voltage Rating	250 V
Contact Material	Cu-Zn
Contact Plating	Gold Plated

### Product Details

RS Pro cable assembly has a 3-Pole M12 straight connector on one end and 3-Pole M12 connector on the other end. This 2 m long cable assembly has nickel plated brass coupling nuts for added durability. The M12 connector boasts a high degree of environmental protection and is ideal for industrial use, with applications ranging from process control to commercial electronics.

### Features and Benefits

- Insulation Resistance >= 100 MΩ
- Neoprene O-Ring
- Brass nickel plated coupling nut

TOLERANCE			
SCALE	UNIT		
DRAW	Brown	DATE	31.10.2018
CHECK	Walter	REV	
		TITLE	
		SM C10 DF12S4-M12S3-02BP34	
		DESCRIPTION	
		2M Cable assembly with a 3 Pole M12 Straight & 3 Pole M12, 4 A, 250 V, IP67	